

## POWERHOUSE INVERTER GENERATOR PH3100Ri 3000 Rated Watts • Remote Control Start

- Remote electric start to 75'; key start and recoil start
- Variable speed for fuel economy as power demands, or constant speed for 100% full power
- Will operate 13,500 BTU RV air conditioners
- Inverter equipped for safe use with electronic equipment
- Low noise; great for campground use
- Powerful 6.8 hp (270cc) engine
- Engine reset button so if the unit is overloaded you don't have to restart the engine
- One 5-20R 20 amp duplex receptacle and one L5-30R 30 amp twist lock receptacle
- Internal circuit breaker
- Fuel gauge
- Hour meter
- Emergency stop control
- Compact and powerful in a case
- Wheels included (2 straight with brake and 2 swivel wheels for ease of transportation)
- Padded handles
- 12 volt external charging system
- EPA, CARB and CSA compliant
- Two year consumer/one year commercial warranty

**69273** 3100 Watt Inverter Generator #PH3100Ri (not UPS-able)



## INVERTER GENERATORS



## POWERHOUSE INVERTER GENERATOR PH2700PRI 2600 Rated Watts • Parallel Ready • Remote Control Start

- Remote electric start to 75'; key start and recoil start
  - Variable speed for fuel economy as power demands, or constant speed for 100% full power
  - Inverter equipped for safe use with electronic equipment
  - Low noise; great for campground use
    - Powerful 5.1 hp (150cc) engine
    - Engine reset button so if the unit is overloaded you don't have to restart the engine
    - One 20 amp duplex receptacle
    - Internal circuit breaker
  - Emergency stop control
- Compact and powerful in a suitcase style case

- Carry handle and roll-along "wheelie" handle
- Textured handle
- Convenient fuel primer bulb
- Covered fuel fill
- 12 volt external charging system
- EPA, CARB and CSA compliant
- Two year consumer/one year commercial warranty

**69272** 2700 Watt Inverter Generator, Parallel Ready #PH2700PRI (not UPS-able)



| FEATURE                                   | PH2700PRi Parallel (69272)                         | PH3100Ri (69273)                                   |
|---|--|--|
| Inverter Equipped                         | Yes  | Yes  |
| Rated Frequency (Hz)                      | 60 Hz  | 60 Hz  |
| Rated Voltage (V)                         | 120 V  | 120 V  |
| Rated Current (A)                         | 21.7 A   | 25 A   |
| Maximum Current (A)                       | 22.5 A   | 25.8 A   |
| Maximum Engine Speed (rpm)                | 5000 rpm   | 3600 rpm   |
| Rated Output (KW)                         | 2.6 KW   | 3.0 KW   |
| Maximum Output (KW)                       | 2.7 KW   | 3.1 KW   |
| DC Output (A)                             | 12 V—8.3 A   | 12 V—8.3 A   |
| Phase                                     | Single   | Single   |
| Electric Circuit Breaker                  | Inverter Controlled & Panel Mounted                | Inverter Controlled & Panel Mounted                |
| Structure                                 | Enclosed   | Enclosed   |
| Starting System                           | Remote, Electric & Recoil                          | Remote, Electric & Recoil                          |
| Engine Type                               | Single Cylinder, 4-Stroke OHC, Air-Cooled Gasoline | Single Cylinder, 4-Stroke OHV, Air-Cooled Gasoline |
| Fuel Tank Capacity (Gal)                  | 1.6 gal  | 4.2 gal.   |
| Ignition System                           | Electronic Ignition                                | Electronic Ignition                                |
| Spark Plug                                | A7RTC  | F7RTC  |
| Noise Level (Zero load/Full load)         | 58–67 dB @23' (7m)                                 | 56–65 dB @23' (7m)                                 |
| Continuous Run Time, Full load (1/4 load) | 3.3 hrs. (8.3 hrs)                                 | 7.3 hrs (17 hrs)                                   |
| Fuel Type                                 | Unleaded Gasoline                                  | Unleaded Gasoline                                  |
| Generator Dimensions (L x W x D)          | 22-7/8" x 12-7/32" x 19-11/16"                     | 23-5/8" x 17-3/4" x 20-1/2"                        |
| Dry Weight (lbs./kg)                      | 77 lbs./35 kg                                      | 129 lbs./59 kg                                     |
| Receptacles                               | One 120V, 20A 5-20R Duplex                         | One 120V, 20A 5-20R Duplex, One 120V, 30A L5-30    |
| Horsepower (hp)                           | 5.1/150cc  | 6.8/270cc  |
| Oil Capacity oz (ml)                      | 16 oz. (473 ml)                                    | 35 oz. (1035 ml or 1L)                             |
| Oil Type                                  | 5W-40  | 5W-40  |
| Certifications                            | EPA, CSA, CARB, ISO 9001-2008                      | EPA, CSA, CARB, ISO 9001-2008                      |
| Primer Bulb                               | Yes  | No   |
| Overload Reset Switch                     | Yes  | Yes  |
| Fuel Gauge                                | No   | Yes  |
| Hour Meter                                | No   | Yes  |
| Fuel Economy Switch                       | Yes  | Yes  |
| Automatic Low Oil Shutdown                | Yes  | Yes  |
| Parallel Ready                            | Yes  | No   |
| Warranty                                  | 2 yr. (1 yr. commercial)                           | 2 yr. (1 yr. commercial)                           |

